

## WFGP Black Opaque Matte

### FACE FILM

Face Film:	Monomeric calendered PVC
Gauge:	70 micron nominal
Tensile Strength	50N/25mm MD/48N/25mm TD nominal
Elongation at break:	180% MD nominal
Shrinkage	Minimal

### ADHESIVE

Type:	Permanent pressure sensitive acrylic
Perceived tack:	Medium
Application Temperature:	+ 5 degreesC

A black opaque obscurity block-out film with a matte finish.

Ideal to create a solid opaque glass effect providing 24-hour privacy of valuable assets or to blank off unsightly parts of a building such as blockwork, partitions, insulation or suspended ceilings.

The vinyl is resistant to most mineral oils, fats and fuels, aliphatic solvents, mild acids, diesel, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.

### **Important Information**

Internal or External application.

The internal application of black film is only recommended if the glass is toughened.

**Please Note: the above is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use, and the purchaser assumes all risks in connection with such use.**

 **0345 337 4751**

 **www.wfprotection.co.uk**



is a trademark of WF Glazing Protection Ltd

WF Glazing Protection Ltd © 2019 | Registered in England and Wales No. 6030388  
NBV Enterprise Centre, David Lane, Nottingham, NG6 0JU