

WFGP Clear UV

<u>Performance Data</u>	<u>Single Pane</u>	<u>Double Pane</u>
Total Solar Energy Rejection	14%	26%
Solar Heat Gain Coefficient (G Value)	0.86	0.74
Visible Light Transmitted	84%	79%
Internal Reflection	9%	10%
UV Rejection	99.8%	99.8%

WFGP Clear UV window film filters nearly all of the harmful Ultra Violet rays to help reduce fading whilst maintaining the natural appearance of the existing window. It can also be used to assist with certain skin conditions sensitive to UV light.

Important Information

Internal application only.

Polyester film is not suitable for application to plastics or polycarbonates.

UV rays, visible light and heat are the main causes of fading. However, they are not the only causes. By reducing these elements fading can be greatly reduced but it is impossible to completely eliminate it.

Please Note: the above is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use, and the purchaser assumes all risks in connection with such use.

 **0345 337 4751**

 **www.wfprotection.co.uk**



is a trademark of WF Glazing Protection Ltd

WF Glazing Protection Ltd © 2019 | Registered in England and Wales No. 6030388
NBV Enterprise Centre, David Lane, Nottingham, NG6 0JU