

WFGP Natural70 HP

| <u>Performance Data</u> | <u>Single Pane</u> | <u>Double Pane</u> |
|--|--------------------|--------------------|
| Total Solar Energy Rejection | 52% | 45% |
| Solar Heat Gain Coefficient (G Value) | 0.48 | 0.55 |
| Visible Light Transmitted | 67% | 61% |
| Internal Reflection | 14% | 18% |
| UV Rejection | 99% | 99% |
| Glare Reduction | 25% | 24% |

WFGP Natural70 High Performance is a virtually clear window film with a spectrally selective, multi alloy, low reflection coating. The film is designed to maximise comfort by reducing solar heat gain without compromising natural light. The rejection of solar energy as well as harmful Ultra Violet rays also provides higher fade protection levels than standard clear UV films.

Important Information

Internal application only.

We do not recommend the use of internally installed solar reflective film on Georgian Wired glass or double-glazed units if they are Laminated glass due to the increased risk of thermal fracture.

Polyester film is not suitable for application to plastics or polycarbonates.

UV rays, visible light and heat are the main causes of fading. However, they are not the only causes. By reducing these elements fading can be greatly reduced but it is impossible to completely eliminate it.

Please Note: the above is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use, and the purchaser assumes all risks in connection with such use.

 **0345 337 4751**

 **www.wfprotection.co.uk**



is a trademark of WF Glazing Protection Ltd

WF Glazing Protection Ltd © 2019 | Registered in England and Wales No. 6030388
NBV Enterprise Centre, David Lane, Nottingham, NG6 0JU