

# **WFGP Temp-Protect Clear**

### **FACE FILM**

Caliper 90 Microns (+/-10%)

Substance 125 gsm (+/-10%)

Shrinkage

Recommended Life 3 years

#### **ADHESIVE**

Adhesive Type

Modified acrylic removable with good clarity, offering clean removal from glass, laminated plastics, cross linked enamels. Not suitable on papers, PVC and air-dried paints and varnishes

Tack FTM9 2 N/sq inch

Ultimate Adhesion FTM2 2 N/sq inch

Resistance to Sunlight Medium

+ 5 degreesC **Application Temperature** 

Service Temperature -40 to +120 degreesC

Cohesive Strength

## RELEASE LINER

Type of Backing White, silicone glassine calendered kraft

Substance 65 gsm (+/-10%)

Caliper 55 microns (+/-10%)

Temp-Protect Clear is a temporary protection vinyl film to help guard against scratches, plaster and paint with a low-tack adhesive for easy removal afterwards.

An ideal solution for the short-term protection of glass during construction type works whilst maintaining natural light.

## **Important Information**

Internal or external application.

Please Note: the above is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use, and the purchaser assumes all risks in connection with such use.



2**/** 0345 337 4751



