

WFGP White Opaque Matte

FACE FILM

Face Film:	Monomeric calendered PVC
Gauge:	70 micron nominal
Tensile Strength	50N/25mm MD/48N/25mm TD nominal
Elongation at break:	180% MD nominal
Shrinkage	Minimal

ADHESIVE

Type:	Permanent pressure sensitive acrylic
Perceived tack:	Medium
Application Temperature:	+ 5 degreesC

A white opaque obscurity block-out film with a matte finish.

Ideal to create a solid opaque glass effect providing 24-hour privacy of valuable assets, personal modesty or hide unattractive parts of a building.

The vinyl is resistant to most mineral oils, fats and fuels, aliphatic solvents, mild acids, diesel, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.

Important Information

Internal or External application.

We do not recommend the use of internally installed solar reflective film on Georgian Wired glass or double-glazed units if they are Laminated glass due to the increased risk of thermal fracture.

Please Note: the above is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use, and the purchaser assumes all risks in connection with such use.

 **0345 337 4751**

 **www.wfprotection.co.uk**



is a trademark of WF Glazing Protection Ltd

WF Glazing Protection Ltd © 2019 | Registered in England and Wales No. 6030388
NBV Enterprise Centre, David Lane, Nottingham, NG6 0JU